ALT ANL PT Series

Blade Fuses – 58V/80V

Specification for approval

规格承认书



产品名称：ALT 58V/80V ANL PT系列 大号插栓车用保险丝

Product Type: ALT 58V/80V ANL PT Series Bolt Auto Fuse

ALT ANL PT Series

Blade Fuses – 58V/80V

1 适用范围 Scope of application

1.1 汽车照明，音响，汽车防盗器，充电保护，电池管理系统保护, UPS 等汽车低压电路，其他低压电子产品，小型变压器，电动玩具，充电器等。各颜色标示的安培值易辨认更换。

Suitable for auto lighting, auto guard against theft,Charging protection,BMS Protection,UPS etc Also applied to low voltage electronic products, little transformers, electronic toys, chargers and so on. Blade fuses are color-coded for easy amperage identification. Instead.

1.2 AOLITTEL ANL系列电动汽车保险丝经过特殊设计和测试，可在保护电动汽车和混合动力电动汽车的大功率电池充电和管理系统方面提供一流的保护性能，额定电流从25A到600A，最高可达80VDC。

AOLITTEL ANL series EV fuses are specially engineered and tested to provide best-in-class protection performance in protecting high power battery charging and managing systems of Electrical Vehicles and Hybrid Electrical Vehicles, up to 80VDC in ratings from 25A to 600A.

2 功能特性 Features

电压：58V/80VDC Automotive fuse

电流：Rated Current: 25-600 A

螺栓尺寸：Bolt Size: M8

扭矩：Torque: M8:12N.m

使用温度：Operating Temperature: -40 to 125°C degrees

分断：Rated Breaking Capacity: 2.7 kA at 58V/80VDC

适配保险丝座：ANL-H;BHR059-25-M6; BHR051-25- M8; BFR050-28-M6

Recommended fuse holder: AAM; BHR059-25-M8; BHR051-25-M8; BFR050-28-M8

3 相关标准及认证 Relevant Standards and Certification

3.1 执行标准 Standards：UL248, ISO8820-5, IATF 16949

3.2 认证 Certification：

证书 Certification	认证范围 Scope of Certification	证书编号 Certification No.
CE	25A~600A	SZEM2412011065BAV
ROHS	25A~600A	CANEC26013537704

ALT ANL PT Series

Blade Fuses – 58V/80V

4 结构及尺寸 Structure and Size (unit: mm)

示列图 Display





5 原材料明细 Material Details

编号 No.	零件名称 Part Name	材质 Material
①	陶瓷外壳 Ceramic crust	陶瓷 Ceramic
②	铜带 Copper piece	铜合金 Copper alloy

6 标示和外观 Marking and appearance

6.1 保险丝上的标记应清晰 The marking on the fuse should be clear.

6.2 保险丝塑料外壳应有如下标记:There should be the following marks on the fuse:
额定电流 Rated current: **300A(示例Display)**

6.3 保险丝外观干净无污点、氧化等，塑料外壳应无破裂。污染等现象。
The appearance of the fuse should be clean and have no stain , oxidizing , etc . The plastic crust Should not have been broken， polluted etc.

7 电气特性 Electrical characteristics

7.1 实验条件 Test condition
所有测试环境温度25±5℃。
All electrical characteristics tests are conducted at an ambient temperature of 25±5℃.

7.2 塑料外壳颜色:白 Plastic crust color : White **(示例Display)**

ALT ANL PT Series

Blade Fuses – 58V/80V

7.3 时间-电流特性 Time-Current Characteristics

额定电流的% % of ampere rating	额定电流 Rated current	熔断时间 Opening time
150%	25A-225A	≥1H
220%	225A-600A	≤60s
250%	25A-600A	0.8s~10s
400%	25A-600A	0.2s~2s

7.4 如需要特定电流时间测试，我们可提供对应实验数据 If specific current-time testing is required, we can provide corresponding experimental data

8 环境特性 Environmental characteristics

8.1 使用温度范围

Operating Temperature -40℃～125℃。

8.2 保存条件 Storage Conditions

相对湿度≤75%，可存放 3 年。 Relative humidity≤75%, store 3 years .

9 电气规格 – 表 1 Electrical Specifications-Table 1

Material number 物料编号	Current Rating 额定值	Breaking Capacity	Volt 电压
ANL025PT	25	2.7KA	58V 80V DC
ANL030PT	30		
ANL035PT	35		
ANL040PT	40		
ANL050PT	50		
ANL060PT	60		
ANL070PT	70		
ANL080PT	80		
ANL100PT	100		
ANL125PT	125		
ANL130PT	130		
ANL150PT	150		
ANL175PT	175		
ANL200PT	200		
ANL225PT	225		
ANL250PT	250		
ANL275PT	275		
ANL300PT	300		
ANL350PT	350		
ANL400PT	400		
ANL450PT	450		
ANL500PT	500		
ANL600PT	600		

ALT ANL PT Series

Blade Fuses – 58V/80V

10 包装 Packing

最小包装为：500 个 MOQ: 500PCS

重量预计 1.4KG Weight 1.4 KG

A. Plastic bags：	B. Outer carton：
L29.0±2 * W22.0±2	L43.5±5 * W27.5±5 * H19.5±5





11 时间电流曲线图 Time- current curve.





12 环保标准 Environmental standards

环保文件以附件附送，每年更新一次.

The environmental protection documents are attached and updated annually

- 备注：根据使用条件的不同，以上特性也会相应的变化。
  Remark: Characteristics of fuses according to use conditions may change.
  大于200A的熔体不允许用额定电流持续加载，允许的承载能力由导线决定。
  该熔体仅做短路保护使用。
  Fuse elements above 200A are for short-circuit protection only and are not intended for continuous current loading. The allowable load depends on the connected conductor.

13 其他 / Others

13.1 如果在使用中有超出本规格书的要求，须经双方协商确认。

In the event that an impropriety is found beyond this specification, it shall be fixed by mutual agreement between the parties.

13.2 如果本规格书有不适当的情况，须通过双方协商并由本公司修改。

In the event that an impropriety is found in this specification, AOLITTEL ELECTRONIC CO., LTD. shall amend it by mutual agreement between the parties.

14 CE证书 / Appendix I: CE certificates